

SMART PLUG™ ROOF PATCH

Overview

The Quarrix Smart Plug™ Roof Patch is the smartest solution for covering holes in the roof – FAST! It easily installs in seconds – Place It – Nail It – Done! It is an easy plug solution that makes converting from static vents to ridge ventilation products faster and stronger than other methods. Cutting and bracing plywood to fit the hole is time-consuming and covering it with sheet metal does not meet most local building codes. Can be installed with a nail gun; available in 8” and 12” sizes.



Quarrix Smart Plug Roof Patch Benefits

- Proven Strength**
 Holds more than 700 lbs.
- Perfect Replacement**
 Fits standard sized holes left by box, slant-back or turbine vents.
- System Solution**
 The perfect solution when converting from static vents to ridge ventilation products.
- Complete the Job Faster**
 Installs in seconds, saving you time and money.

THE SMART WAY TO CONVERT STATIC VENTS




8” Smart Plug™
 Designed for patching holes left by box and slant-back vents. Fills holes up to 8” x 8”



12” Smart Plug™
 Ideal size for filling holes left by turbine vents. Fills holes up to 12” x 12”




Remove it.



Place it.



Nail it.



Done.

SMART PLUG ROOF PATCH SPECIFICATIONS

Part #	Patch Size	Outside Dimensions	Wood Dimensions	Thickness	Material	Weight Limit
99008	8 x 8 in 20.32 x 20.32 cm	12 x 12 in 30.48 x 30.48 cm	7-7/8 x 7-7/8 in 20 x 20 cm	7/16 in 1 cm	24 Gauge Galvanized Steel and 7/16” OSB Sheeting	Over 700 lbs. 317.51 kg
99012	12 x 12 in 30.48 x 30.48 cm	16 x 16 in 40.64 x 40.64 cm	11-7/8 x 11-7/8 in 30.16 x 30.16 cm	7/16 in 1 cm	24 Gauge Galvanized Steel and 7/16” OSB Sheeting	Over 700 lbs. 317.51 kg

SS-PLUG11-12.1.16